

CLUB FJ SPECIFICATIONS

Standing Rigging and Halyards

SHROUDS

Wire	1/8" 1x19
Top End	Nico pressed loop w/thimble
Bottom End	Swaged marine eye
Length	12' 10-1/2" (measured bearing point to bearing point)

FORESTAY

Wire	1/8" 1x19
Top End	Nico pressed loop w/thimble
Bottom End	Swaged aircraft eye
Length	13' 5-1/2" (measured bearing point to bearing point)

JIB HALYARD

Wire	1/8" 7x19
Top End	RL382BWL shackle, swaged ball w/shank
Bottom End	Nico pressed loop (no thimble)
Adjusters	Three (3) swaged balls w/shank spaced 1-1/4" apart with topmost ball 5-1/2" above end of nico pressed loop.
Length	14' 3-3/4" (measured from end of lower loop to top of upper swage ball). 14'x5/32"
Tail	Prestretch line attached to loop with two bungee clips (crimps).

MAIN HALYARD

Wire	3/32" 7x19
Top End	RL382AWL shackle, swaged ball w/shank.
Bottom End	Nico pressed loop (no thimble).
Length	7" (measured from bearing point to nico sleeve to top of upper swage ball).
Tail	37' x 5/32" Prestretch line attached to loop with two bungee clips (crimps).